

BEAM - QUICKSHIP

Exterior/Interior Sconce



9777 Reavis Park Drive

St. Louis, MO 63123

800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

GENERAL SPECIFICATION

LED: High efficiency mid-power LEDs are field serviceable.

LED Dimming: 0-10V dimming standard.

Body: Extruded aluminum wall plate and rails. Body hinges for easy serviceability.


Diffuser: Extruded polycarbonate lens is UL-94 HB Flame Class rated.

Standard Finishes: Highly durable oven cured no VOC premium powder coat.

Design: Aluminum die cast end caps and decorative bars.

Exterior Mounting: Gasketed between wall and wall plate.

Listing: Fixture ETL listed for wet locations.



SAMPLE CATALOG NUMBER:						
GL-5451-		H-	S-	DBZ-	A-	
MODEL NO.		LAMPING	DIFFUSER	FINISH	DESIGN	
GL-5450	W in 7 1/4" mm 185	B. 14LED35	Standard: S. Satin White Polycarbonate is UL-94 HB Flame Class rated.	Standard: Powder Coat BLK -Black BL -Blue GR -Gray LG -Light Gray BE -Beige PAB -Antique Brass PA -Painted Aluminum PTC -Painted Copper WH -White DBZ -Dark Bronze NSN -New Satin Nickel BRN -Brown RD -Red CH -Champagne RG -Reed Green SG -Sungold GM -Gun Metal POR -Oil Rubbed Bronze Textured Powder TLV -Light Verdigris TWH -Textured White TBL -Textured Black TS -Textured Silver TBN -Terra Brown TBZ -Textured Bronze	A. Standard	A. No Options
	4lbs H in 17" mm 430					
	2.3kg D in 3 7/8" mm 125					
GL-5451	W in 7 1/4" mm 185	H. 28LED35				
	7lbs H in 25" mm 635					
	3.2kg D in 3 7/8" mm 125					

All dimensions are nominal.

Light Source Definition

Lamp	LED	CRI	Rated Life Hrs	Delivered Lumens	Kelvin	Lamp	LED	CRI	Rated Life Hrs	Delivered Lumens	Kelvin
14LED35	14W	80	50000	781	3500	28LED35	28W	80	50000	1562	3500
Universal Voltage unless otherwise specified.											