## **PIONEER**

## **Indoor Pendant**

9777 Reavis Park Drive St. Louis, MO 63123 800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

## **GENERAL SPECIFICATION**

Acrylic: Acrylic is UL-94 HB Flame Class rated. Available with 3-Form.

Cable Hanger Option: Comes with 72" cable and white cord for


on-site adjustability.

Canopy: Matches fixture finish. Low profile canopy may be mounted on

flat or sloped ceilings up to 40°.

Modifications: Available in .080 satin aluminum. Consult factory for

material change.



SAMPLE CATALOG NUMBER:						
GL-2520-	IN1-	W-	NSN-	1-	Α-	024
MODEL NO.	LAMPING	ACRYLIC	FINISH	HANGER	OPTION(S)	OVERALL HEIGHT
GL-2520 W in 6 1/4" mm 160  12lbs B in 13" mm 330  5kg H in 24" mm 610	IN1. 1MED	Standard: W White Opal S Satin White  3-Form: 3N Linen  Contact factory for 3-Form or .080 Aluminum  Acrylic is UL-94 HB Flame Class rated.	Standard: Powder Coat BLK-Black BL-Blue GR-Gray LG-Light Gray BE-Beige PAB-Antique Brass PA-Painted Aluminum PTC-Painted Copper WH-White DBZ-Dark Bronze NSN-New Satin Nickel BRN-Brown RD-Red CH-Champagne RG-Reed Green SG-Sungold GM-Gun Metal POR-Oil Rubbed Bronze Textured Powder TLV-Light Verdigris TWH-Textured White TBL-Textured Black TS-Textured Black TS-Textured Bronze Premium: SA-Satin Aluminum	2. Cable Standard White Power Cord	A. No Options  BC. Black Cord Fixture supplied with black power cord.  LC. 150" Cord & Cable Fixture supplied with 150" of cable and standard white cord or optional black cord.	Stem mount only - Specify overall height in inches. Standard overall height shown by model no.

All Dimensions are nominal. 120V only\*

## Light Source Definition

Code Lamp Lamp Base
IN1 A-19 Medium