

SELENE WARM DIM

Inner Acrylic Interior Pendant



9777 Reavis Park Drive

St. Louis, MO 63123

800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

GENERAL SPECIFICATION

Warm Dim: LED option (WD) features warm dimming technology that dims smoothly from 3500K-1800K with standard 0-10V dimming.

LED Dimming: Standard 0-10V dimming. TRIAC, DALI, or DMX available upon request.


Acrylic: Satin white seamless outer acrylic is UL-94 HB Flame Class rated.


Cable Hanger: Comes with 72" cable and cord for on-site adjustability.

Canopy: Matches fixture finish.

Finish: Highly durable oven cured no VOC premium powder coat.

Body: Ring spun in 1/8" aluminum.



SAMPLE CATALOG NUMBER: GL-2581-					WD8-	PTC-	1-	A-
MODEL NO.					LAMPING	FINISH	HANGER	OPTIONS
GL-2580 W in 26" mm 660 20lbs B in 7 1/2" mm 190 9kg H in 20"-68" mm 510-1730 Fixture supplied with 72" of cord and cable. Adjust on-site. Minumum 20" OAH. Contact factory for OAH greater than 68".					WD6	Standard: Powder Coat BLK -Black BL -Blue GR -Gray LG -Light Gray BE -Beige PAB -Antique Brass PA -Painted Aluminum PTC -Painted Copper WH -White DBZ -Dark Bronze NSN -New Satin Nickel BRN -Brown RD -Red CH -Champagne RG -Reed Green SG -Sungold GM -Gun Metal POR -Oil Rubbed Bronze Textured Powder TLV -Light Verdigris TWH -Textured White TBL -Textured Black TS -Textured Silver TBN -Terra Brown TBZ -Textured Bronze	1. Cable  2. Vertical Cable 	A. No Options EL. Emergency Ballast Integrally operates two LED strips. Integral test switch. Specify voltage after code. Available GL-2581 only. BC. Black Cord Fixture supplied with black power cord. LC. 150" Cord & Cable Supplied with 150" Cord & Cable.
GL-2581 W in 37" mm 940 30lbs B in 7 1/2" mm 190 13.5kg H in 20"-68" mm 510-1730 Fixture supplied with 72" of cord and cable. Adjust on-site. Minumum 20" OAH. Contact factory for OAH greater than 68".								

All Dimensions are nominal.

Light Source Definition

Code	Total Wattage	CRI	Rated Life Hrs	Delivered Lumens	Kelvin
WD6	124	+80	50000	5362	3500-1800
WD8	165	+80	50000	6669	3500-1800

Universal Voltage unless otherwise specified.