

# SOUTHFIELD

## Indoor Pendant



9777 Reavis Park Drive

St. Louis, MO 63123

800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

### GENERAL SPECIFICATION

**LED:** High efficiency mid-power LEDs are field serviceable.

**LED Dimming:** Standard 1% 0-10V dimming. TRIAC, DALI, or DMX available upon request.

**Down Light:** 90CRI 17 watt 2000 lumen module. Lamping code ending with "DL" includes downlight.

**Acrylic:** Seamless acrylic is UL-94 HB Flame Class rated.


**Canopy:** Matches fixture finish. Low profile canopy may be mounted on flat or sloped ceilings up to 40°. Available stem or field adjustable cord and cable.

**Cable Hanger Option:** Supplied with standard 72" white cord and cable. Field adjustable.

**Finish:** Highly durable oven cured no VOC premium powder coat.

**Modifications:** Consult factory for lamping or cluster options.

**Surge Protection:** External surge protector provided as standard.



### SAMPLE CATALOG NUMBER:

GL-2440-

A-

W-

NSN-

1-

A-

40

MODEL NO.	LAMPING	ACRYLIC	FINISH	HANGER	OPTION(S)	OVERALL HEIGHT
<b>GL-2440</b> 12lbs W in 10 1/2" mm 265 6 kg B in 26" mm 650 H in 37" mm 940  Fixture does not include downlight	<b>U.</b> 4LED30 <b>V.</b> 4LED35 <b>W.</b> 4LED40 <b>T.</b> RGB	<b>Standard:</b> <b>W</b> White Opal <b>S</b> Satin White  Acrylic is UL-94 HB Flame Class rated.	<b>Standard:</b> Powder Coat <b>BLK</b> -Black <b>BL</b> -Blue <b>GR</b> -Gray <b>LG</b> -Light Gray <b>BE</b> -Beige <b>PAB</b> -Antique Brass <b>PA</b> -Painted Aluminum <b>PTC</b> -Painted Copper <b>WH</b> -White <b>DBZ</b> -Dark Bronze <b>NSN</b> -New Satin Nickel <b>BRN</b> -Brown <b>RD</b> -Red <b>CH</b> -Champagne <b>RG</b> -Reed Green <b>SG</b> -Sungold <b>GM</b> -Gun Metal <b>POR</b> -Oil Rubbed Bronze  <b>Textured Powder</b> <b>TLV</b> -Light Verdigris <b>TWH</b> -Textured White <b>TBL</b> -Textured Black <b>TS</b> -Textured Silver <b>TBN</b> -Terra Brown <b>TBZ</b> -Textured Bronze  <b>Premium:</b> <b>SA</b> -Satin Aluminum	<b>1. Stem</b>  Remote driver. <b>2. Cable</b>  Standard white power cord. Remote driver. <b>3. Oversized with Stem</b>  12.5" Canopy <b>4. Oversized with Cable</b>  Standard white power cord. 12.5" Canopy.	<b>A.</b> No Options <b>EL.</b> Emergency LED Remote mount up to 10' from light source in controlled environment with an area temperature range of 32°-131°F. Specify 120 or 277 voltage. <b>BC.</b> Black Cord Fixture supplied with black power cord. <b>LC.</b> 150" Cord & Cable Fixture supplied with 150" of cable and standard white cord or optional black cord.	Standard overall height shown by model no.  For custom overall height, specify in inches.
<b>GL-2441</b> 21lbs W in 10 1/2" mm 265 10 kg B in 35 1/4" mm 895 H in 46" mm 1170  Fixture includes downlight	<b>AA.</b> 4LED30DL <b>BB.</b> 4LED35DL <b>CC.</b> 4LED40DL <b>T.</b> RGB				Hanger options 1 & 2 supplied with remote driver box.	

All dimensions are nominal.

### Light Source Definition

Code	Total Wattage	Delivered Lumens	Kelvin	Code	*Total Wattage	*Delivered Lumens	Kelvin
U	51W	5556	3000	AA	68W	7248	3000
V	51W	5556	3500	BB	68W	7248	3500
W	51W	5556	4000	CC	68W	7248	4000
RGB	Contact Factory for Details						

Universal Voltage unless otherwise specified. \*Includes downlight wattage (17W) and lumen output (1692lm)