

# SOUTHGATE

## Indoor Pendant



9777 Reavis Park Drive

St. Louis, MO 63123

800.331.2425 or 314.631.6000

sales@lighting.com www.lighting.com

### GENERAL SPECIFICATION

**LED:** High efficiency mid-power LEDs are field serviceable. Universal voltage.

**LED Dimming:** Standard 1% 0-10V dimming with LED lamping option.


**Body:** Ring spun in 18ga steel or .050 aluminum.  
Closed body with LED lamping.

**Canopy:** Low profile. May be mounted on flat or sloped ceilings up to 40°.

**Acrylic:** Seamless acrylic is UL-94 HB Flame Class rated.

**Finish:** Highly durable oven cured no VOC premium powder coat.

**Surge Protection:** External surge protector provided as standard.



Textured white pan with LED lamping



SAMPLE CATALOG NUMBER:						
MODEL NO.	LAMPING	ACRYLIC	FINISH	HANGER	OPTION(S)	OVERALL HEIGHT
<b>GL-2210</b> 14lbs B in 18" mm 460 6 kg W in 22 1/2" mm 570 D in 6 3/8" mm 160 H in 29" mm 740	<b>IN3.</b> 3MED <b>F4.</b> 4CF <b>L50.</b> 5LED30 <b>L55.</b> 5LED35 <b>L54.</b> 5LED40	<b>Standard:</b> <b>S.</b> Satin White <b>Optional:</b> <b>W.</b> White Opal <b>F.</b> Faux Alabaster <b>M.</b> Earth Marble	<b>Standard:</b> Powder Coat <b>BLK-</b> Black <b>BL-</b> Blue <b>GR-</b> Gray <b>LG-</b> Light Gray <b>BE-</b> Beige <b>PAB-</b> Antique Brass <b>PA-</b> Painted Aluminum <b>PTC-</b> Painted Copper <b>WH-</b> White <b>DBZ-</b> Dark Bronze <b>NSN-</b> New Satin Nickel <b>BRN-</b> Brown <b>RD-</b> Red <b>CH-</b> Champagne <b>RG-</b> Reed Green <b>SG-</b> Sungold <b>GM-</b> Gun Metal <b>POR-</b> Oil Rubbed Bronze <b>Textured Powder</b> <b>TLV-</b> Light Verdigris <b>TWH-</b> Textured White <b>TBL-</b> Textured Black <b>TS-</b> Textured Silver <b>TBN-</b> Terra Brown <b>TBZ-</b> Textured Bronze <b>Premium:</b> <b>SA-</b> Satin Aluminum <b>SB-</b> Satin Brass <b>PB-</b> Polished Brass <b>ORB-</b> Oil Rubbed Bronze <b>PC-</b> Polished Copper <b>SA-</b> Satin Aluminum <b>SC-</b> Satin Chrome <b>SN-</b> Satin Nickel	<b>1. Stem</b> <b>2. Cable</b> <b>3. Arms</b> <b>4. Stem Cluster</b>	<b>A.</b> No Options <b>F.</b> Add Finial <b>B.</b> Damp Location Available in powder coat or Satin Aluminum finish. <b>DE.</b> ECO Dimming Lutron Ecosystem dimming CF lamping option. Specify voltage and wattage after dimming code. <b>DV.</b> Mark VII Dimming Advance Mark VII dimming CF lamping option. Specify voltage and wattage after dimming code. <b>DX.</b> Mark X Dimming Advance Mark X dimming CF lamping option. Specify voltage and wattage after dimming code. <b>E.</b> Emergency Ballast Operates one fluorescent lamp. Remote mount up to 5' from lamps in controlled environment with an area temperature range of 32°- 131°F. Non-dimming compact fluorescent only. Specify 120 or 277 voltage. <b>EL.</b> Emergency LED Remote mount up to 10' from lamping in controlled environment with an area temperature range of 32°-131°F. LED only. Specify 120 or 277 voltage. <b>P.</b> Perforated Top Lens CF and INC only Multi-circuiting available upon request.	Standard overall height shown by model no.  For custom overall height, specify in inches.
<b>GL-2211</b> 21lbs B in 24" mm 610 10 kg W in 30" mm 760 D in 7 3/8" mm 190 H in 34" mm 865	<b>IN3.</b> 3MED <b>F4.</b> 4CF <b>L60.</b> 6LED30 <b>L65.</b> 6LED35 <b>L64.</b> 6LED40	Acrylic is UL-94 HB Flame Class rated.				
<b>GL-2212</b> 29lbs B in 30" mm 760 13kg W in 36" mm 915 D in 8 3/8" mm 215 H in 38" mm 965	<b>IN6.</b> 6MED <b>F4.</b> 4CF <b>L90.</b> 9LED30 <b>L95.</b> 9LED35 <b>L94.</b> 9LED40					
<b>GL-2213</b> 37lbs B in 38" mm 965 17kg W in 44" mm 1120 D in 10" mm 255 H in 42" mm 1070	<b>IN6.</b> 6MED <b>F6.</b> 6CF <b>L120.</b> 12LED30 <b>L125.</b> 12LED35 <b>L124.</b> 12LED40					
38" available in Satin Aluminum and powder coat finish only						

Fixtures over 50 lbs require reinforced junction box  
All dimensions are nominal.

### Lamp Definition

Code	Lamp	Fluorescent	Lamp Base	Lamp Lumens <sup>1</sup>	Code	Total Wattage	Kelvin	Delivered Lumens
F4, F6	CF	CF 26W/32W/42W	GX24q-3/4 4PIN	1530/2040/2690	L50	71	3000	8971
IN3, IN6	Med	A-19	Medium		L55	71	3500	8971
					L54	71	4000	8971
					L60	87	3000	10544
					L65	87	3500	10544
					L64	87	4000	10544
					L90	130	3000	16400
					L95	130	3500	16400
					L94	130	4000	16400
					L120	177	3000	21794
					L125	177	3500	21794
					L124	177	4000	21794

Universal Voltage unless otherwise specified.

<sup>1</sup>Per MAXLITE & GE lamp products catalog

Contact factory for availability of other lamp configurations including induction and metal halide.