

TAHOE II

Interior Square Pendant



9777 Reavis Park Drive

St. Louis, MO 63123

800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

GENERAL SPECIFICATION

LED: High efficiency mid-power LEDs are field serviceable.

LED Dimming: 1% 0-10V dimming standard.

Shade: Standard white fabric shade with integral satin white diffuser.

Custom shapes, sizes, and colors available.

Canopy: Matches fixture finish. Low profile canopy may be mounted on flat or sloped ceilings up to 40°. Available stem or field adjustable cord and cable.


Cable Hanger Option: Supplied with standard 72" white cord and cable.

Field adjustable.

Finish: Highly durable oven cured no VOC premium powder coat.

Modifications: Consult factory for lamping or cluster options.

Surge Protection: External surge protector provided as standard.



SAMPLE CATALOG NUMBER:						
GL-2732-	L55-	W-	NSN-	5-	A-	072
MODEL NO.	LAMPING	SHADE	FINISH	HANGER	OPTIONS	OVERALL HEIGHT
GL-2730 W in 14" 5lbs D in 9.5" 2.25kg H Specify	IN3.3MED* L10.1LED30 L15.1LED35 L14.1LED40	W White C Cream R Red BL Blue O Olive S Stone	Standard: Powder Coat BLK-Black BL-Blue GR-Gray LG-Light Gray BE-Beige PAB-Antique Brass PA-Painted Aluminum PTC-Painted Copper WH-White DBZ-Dark Bronze NSN-New Satin Nickel BRN-Brown RD-Red CH-Champagne RG-Reed Green SG-Sungold GM-Gun Metal POR-Oil Rubbed Bronze Textured Powder TLV-Light Verdigris TWH-Textured White TBL-Textured Black TS-Textured Silver TBN-Terra Brown TBZ-Textured Bronze	1. Stem 5. Cord & Cable Supplied with white cord with hanger option 5.	A. No Options DE. ECO Dimming Lutron Ecosystem dimming CF lamping option. Specify voltage and wattage after dimming code. DV. Mark VII Dimming Advance Mark VII dimming CF lamping option. Specify voltage and wattage after dimming code. DX. Mark X Dimming Advance Mark X dimming CF lamping option. Specify voltage and wattage after dimming code. E. Emergency Remote mount up to 5' from lamps in controlled environment with an area temperature range of 32°-131°F. Compact fluorescent only. Specify 120 or 277 voltage. EL. Emergency LED Must be remotely mounted in a controlled environment with an area temperature range of 32°-131°F. LED only. Specify 120 or 277 voltage. LC. 150" Cord & Cable Supplied with 150" Cord & Cable.	Specify overall height for stem hanger option in inches.
GL-2731 W in 18" 5lbs D in 9.5" 2.25kg H Specify	IN3.3MED* L10.1LED30 L15.1LED35 L14.1LED40					
GL-2732 W in 24" 15lbs D in 11.5" 7kg H Specify	IN3.3MED* L50.5LED30 F4.4CF L55.5LED35 L54.5LED40	Washable: WW White WC Cream WT Tan WB Brown				
GL-2733 W in 30" 18lbs D in 12.5" 8kg H Specify	IN3.3MED* L50.5LED30 F4.4CF L55.5LED35 L54.5LED40					
GL-2734 W in 36" 20lbs D in 13.5" 9kg H Specify	IN6.6MED* L80.8LED30 F6.6CF L85.8LED35 L84.8LED40					
GL-2735 W in 48" 25lbs D in 15.5" 11.5kg H Specify	IN6.6MED* L80.8LED30 F6.6CF L85.8LED35 L84.8LED40					
*120 Volt Only						

All Dimensions are nominal.

Shade

Standard



White



Cream



Blue



Stone



Red



Olive

Washable - Trilam



White



Tan



Cream



Brown

Custom fabrics available upon request. Contact factory. Reproduced graphic representation. Please contact sales@glighting.com for fabric samples.

Light Source Definition

Code	Lamp	Fluorescent	Lamp Base	Lamp Lumens	Code	Lamp	Total Wattage	Delivered Lumens	Kelvin
F4,F6	CF	CF 26W/32W/42W	GX24q-3/4 4PIN	1530/2040/2690	L50	5LED30	72W	7436	3000
IN3,IN6	MED	A-19	Medium		L55	5LED35	72W	7436	3500
		Total	Delivered		L54	5LED40	72W	7436	4000
Code	Lamp	Wattage	Lumens	Kelvin	L80	8LED30	114W	12248	3000
L10	1LED30	27 W	3008	3000	L85	8LED35	114W	12248	3500
L15	1LED35	27 W	3008	3500	L84	8LED40	114W	12248	4000
L14	1LED40	27 W	3008	4000					

Universal Voltage unless otherwise specified.