

TRILOGY

Indoor Pendant



9777 Reavis Park Drive

St. Louis, MO 63123

800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

GENERAL SPECIFICATION

LED: High efficiency mid-power LEDs are field serviceable. Universal voltage.

LED Dimming: Standard 1% 0-10V dimming with LED lamping option.


Body: GL-2110-2113 ring spun in 18ga steel or .050 aluminum. Closed body with LED lamping.

Canopy: Low profile. May be mounted on flat or sloped ceilings up to 40°.

Acrylic: Seamless acrylic is UL-94 HB Flame Class rated.

Finish: Highly durable oven cured no VOC premium powder coat.

Surge Protection: External surge protector provided as standard.



Textured white pan with LED lamping



SAMPLE CATALOG NUMBER:						
GL-2112-	L95-	S-	NSN-	1-	A-	038
MODEL NO.	LAMPING	ACRYLIC	FINISH	HANGER	OPTION(S)	OVERALL HEIGHT
GL-2110 14lbs B in 18" mm 460 6 kg W in 23 1/2" mm 600 D in 7 5/8" mm 195 H in 29" mm 735	IN3. 3MED L50. 5LED30 F4. 4CF L55. 5LED35 L54. 5LED40	Standard: S. Satin White Optional: W. White Opal F. Faux Alabaster M. Earth Marble	Standard: Powder Coat BLK-Black BL-Blue GR-Gray LG-Light Gray BE-Beige PAB-Antique Brass PA-Painted Aluminum PTC-Painted Copper WH-White DBZ-Dark Bronze NSN-New Satin Nickel BRN-Brown RD-Red CH-Champagne RG-Reed Green SG-Sungold GM-Gun Metal POR-Oil Rubbed Bronze Textured Powder TLV-Light Verdigris TWH-Textured White TBL-Textured Black TS-Textured Silver TBN-Terra Brown TBZ-Textured Bronze Premium: SA-Satin Aluminum SB-Satin Brass PB-Polished Brass ORB-Oil Rubbed Bronze PC-Polished Copper SA-Satin Aluminum SC-Satin Chrome SN-Satin Nickel	1. Stem 2. Cable 3. Arms 4. Stem Cluster	A. No Options F. Add Finial B. Damp Location Available in powder coat or Satin Aluminum finish. DE. ECO Dimming Lutron Ecosystem dimming CF lamping option. Specify voltage and wattage after dimming code. DV. Mark VII Dimming Advance Mark VII dimming CF lamping option. Specify voltage and wattage after dimming code. DX. Mark X Dimming Advance Mark X dimming CF lamping option. Specify voltage and wattage after dimming code. E. Emergency Ballast Operates one fluorescent lamp. Remote mount up to 5' from lamps in controlled environment with an area temperature range of 32°- 131°F. Non-dimming compact fluorescent only. Specify 120 or 277 voltage. EL. Emergency LED Remote mount up to 10' from lamping in controlled environment with an area temperature range of 32°-131°F. LED only. Specify 120 or 277 voltage. W. White Opal Top Lens CF and INC only C. Clear Top Lens CF and INC only P. Perforated Top Lens CF and INC only Multi-circuiting available upon request.	Standard overall height shown by model no. For custom overall height, specify in inches.
GL-2111 21lbs B in 24" mm 610 10 kg W in 29 1/2" mm 750 D in 8 5/8" mm 220 H in 34" mm 865	IN3. 3MED L60. 6LED30 F4. 4CF L65. 6LED35 L64. 6LED40	Acrylic is UL-94 HB Flame Class rated.				
GL-2112 29lbs B in 30" mm 760 13kg W in 36 5/8" mm 930 D in 9 5/8" mm 245 H in 38" mm 965	IN6. 6MED L90. 9LED30 F4. 4CF L95. 9LED35 L94. 9LED40					
GL-2113 37lbs B in 38" mm 965 17kg W in 46" mm 1170 D in 11 1/8" mm 285 H in 42" mm 1070	IN6. 6MED L120. 12LED30 F6. 6CF L125. 12LED35 L124. 12LED40 38" available in Satin Aluminum and powder coat finish only					

Fixtures over 50 lbs require reinforced junction box
 All dimensions are nominal.

Lamp Definition

Code	Lamp	Fluorescent	Lamp Base	Lamp Lumens ¹	Code	Total Wattage	Kelvin	Delivered Lumens
F4, F6	CF	CF 26W/32W/42W	GX24q-3/4 4PIN	1530/2040/2690	L60	87	3000	10544
IN3, IN6	Med	A-19	Medium		L65	87	3500	10544
					L64	87	4000	10544
					L90	130	3000	16400
					L95	130	3500	16400
					L94	130	4000	16400
					L120	177	3000	21794
					L125	177	3500	21794
					L124	177	4000	21794

¹Per MAXLTE & GE lamp products catalog
 Contact factory for availability of other lamp configurations including induction and metal halide.

Universal Voltage unless otherwise specified.